

# M2C-PPC-19 (K)

## 7th Generation Intel® Core™ Processors



### Dimensions

- Length x Width x Height: 485 x 445 x 84 mm
- Cutout (W x H): 439 x 399 mm
- Weight: 10,5 kg ± 10%

### Housing

- Chassis: Aluminium, RAL 9005 powder coated
- Cover electronics: Steel, RAL 9005 powder coated
- Front: Glass, antireflex coated both sides

### Display

- 19" TFT Display
- LED Backlight
- Resolution: 1280 x 1024
- Brightness: 300 cd/m<sup>2</sup>
- Full range dimming: 0-100 %
- With or without Resistive Touch

|                              |                    |  |   |
|------------------------------|--------------------|--|---|
| <b>System</b>                | Processor          | 7th Generation Intel® Core™ Processors<br>Intel® Core™ i7-7600U, 2 Cores, 4M Cache, 2.80 GHz up to 3.90 GHz<br>Intel® Core™ i5-7300U, 2 Cores, 3M Cache, 2.60 GHz up to 3.50 GHz<br>Intel® Core™ i3-7100U, 2 Cores, 3M Cache, 2.40 GHz<br>Intel® Celeron® 3965U, 2 Cores, 2M Cache, 2.20 GHz |   |
|                              | Memory             | Up to 32GB, Dual Channel DDR4 1866/2133MHz   |   |
|                              | Storage            | 1 x M.2 SSD up to 1TB or SATA3.0/PCIe Gen3 x2 NVMe<br>2 x SSD up to 2TB RAID 0/1/5   |   |
| <b>Graphics</b>              | Controller         | Intel® HD Graphics GT Series   |   |
|                              | Feature            | OpenGL 4.4, DirectX 12, OpenCL 2.1<br>HW Decode: AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9<br>HW Encode: AVC/H.264, MPEG2, JPEG, HEVC/H265, VP8, VP9   |   |
|                              | Dual Displays      | 2 x DP++   |   |
| <b>Expansion</b>             | Interface          | 1 x PCIe x4 (Gen 3) Low Profile  |   |
| <b>Rear I/O</b>              | Ethernet           | 2 x GbE (RJ-45)  | Optional up to 4 x GbE                    |
|                              | USB                | 4 x USB 3.0  | Optional up to 8 x USB                    |
|                              | Display            | 2 x DP++   |   |
|                              | Audio              | 1 x Line-out 1 x Mic-in  |   |
|                              | Serial             |  | Optional up to 4 x COM (RS232 or 422/485) |
| <b>Optional (M2 CB)</b>      | Controller         | M2 Controller Board  |   |
|                              | Feature            | 1 x Internal Alarm-Buzzer<br>1 x Out for ext. Alarm-Buzzer<br>1 x Potentiometer In, 2 x Push Button In<br>2 x Out for Status LED   |   |
| <b>Watchdog Timer</b>        | Output & Interval  | System Reset, Programmable via Software from 1 to 255 Seconds  |   |
| <b>Security</b>              | TPM                | TPM 2.0 (Opt.)   |   |
| <b>Power Options</b>         | DC                 | 24 VDC   |   |
|                              | AC                 | 230/115 VAC (50/60Hz)  |   |
|                              | DCAC               | 24 VDC + 230/115 VAC (redundant)   |   |
| <b>OS Support</b>            | Microsoft/ Linux   | Windows 10<br>Linux  |   |
|                              | <b>Environment</b> | Operating Temp.  | -15 to +55°C                              |
|                              | Storage Temp.      | -20 to +70°C   |   |
|                              | IP Rating          | IP66 (front) - IP20 (rear)   |   |
| <b>Compass Safe Distance</b> | Standard Compass   | 1.00 m in all directions   |   |
|                              | Steering Compass   | 0.80 m in all directions   |   |
| <b>Type Approval</b>         |                    | DNV, Tested according to EN 60945<br>EU-RO-MR(*)   |   |

(\*) expected Q2/2024



Options and additional features are configurable. Contact your Sonove sales representative for further information. Depending on the product configuration, interfaces or slot brackets may differ from the figures in this document.

# M2C-PPC-19 (K)

7th Generation Intel® Core™ Processors



## Drawings Standard





# M2C-PPC-19 (K)

7th Generation Intel® Core™ Processors



## Drawings 4HF



Sonove GmbH  
Hindelanger Str. 33  
87527 Sonthofen  
Deutschland

Tel. +49 8321 67466 200  
Fax +49 8321 67466 199  
marine@sonove.com